

Bearing Number	Dimensions (mm)				Loads (KN)		Permissible speed	
	d	D	B	r(smin)	Cr	Cor	Grease	Oil
6302N	15	42	13	1	11.4	5.45	17000	21000
6203N	17	43	12	0.6	9.6	4.6	18000	21000
6303N	17	47	14	1	13.5	6.55	11000	19000
6403N	17	62	17		22.7	10.8	11000	15000
6004N	20	47	12	0.6	12.8	6.65	18000	21000
60/22N	22	44	12	0.6	9.8	5.05	14000	17000
62/22N	22	50	14	0.6	12.9	6.8	14000	17000
16005N	25	47	8	0.3	6.95	4.6	15000	18000
6005N	25	47	12	0.6	7.74	4.96	15000	18000
63/25N	25	62	16	0.3	21.2	10.9	12000	14000
6405N	25	80	21		38.2	19.2	8500	11000
60/29N	29	52	12	0.6	12.5	7.4		
6906N	30	47	9	0.3	7.25	5	14000	17000
16006N	30	55	9	0.3	9.95	6.55	13000	15000
6006N	30	55	13	1	13.2	8.3	13000	15000
63/30N	30	68	18	0.3	35.8	19		
6406N	30	90	23	1.5	47.5	24.5	8000	10000
60/32N	32	58	13	1	15	9.15		
6807N	35	47	7	0.3	4.75	3.8	14000	16000
6907N	35	55	10	0.6	10.4	7.15	12000	15000
16007N	35	62	9	0.3	11.7	8.15	12000	14000
6007N	35	62	14	1	16	10.3	12000	14000
63/35-ZN	35	80	21	1.5	39.7	21.6		
6407N	35	100	25	0.3	56.8	29.5		6500
16008N	40	68	9	0.3	11.1	8.55	10000	12000
6008N	40	68	15	1	16.8	11.5	10000	12000
6408N	40	110	27	1.3	65.5	37.5	6300	8000
6809N	45	58	7	0.3	5.35	4.9	11000	13000
6909N	45	68	12	0.6	14.1	10.9	10000	12000
16009N	45	75	10	0.6	12.9	10.5	9200	11000
6009N	75	75	16	1	20.9	15.2	9200	11000
6010N	50	80	16	1	21.8	16.6	5000	10000
6210N	50	90	20	1.1	35	23.2	7100	8600
6410N	50	130	31		92.2	55.2	5300	6300
6811N	55	72	9	0.3	8.8	8.1	8700	10000
6911N	55	80	13	1	16	16.2	8200	9600
16011N	55	90	11	0.6	15.2	13.5	7700	90000
6011N	55	90	18	1.1	29.3	21.3	7700	90000
6311N	55	120	29	2	71.5	45	5800	6800
6411N	55	140	33		100	62.5	4800	6000
6812N	60	78	10	0.3	11.5	10.6	8000	9500
6912N	60	85	13	1	15.2	13.5	7600	9000
16012N	60	95	11	0.6	16.2	14.3	7100	8500
6012N	60	95	18	1.1	29.4	23.2	7100	8500
6212N	60	110	22	1.5	52.5	36	6000	7100
6312N	60	130	31	2.1	82	52	5400	6300
6412N	60	150	35		109	70	4500	5600
6813N	65	85	10	0.6	11.9	11.5	7500	8700
6913N	65	90	13	1	17.4	16	7100	8500
16013N	65	100	11	1	20.5	18.6	67200	8000
6013N	65	100	18	1.1	30.5	25.2	6700	8000
6313N	65	140	33	2.1	92.5	59.5	4900	6000
6316N	65	140	33	2.1	92.5	59.5	3400	6000

6413N	65	160	37	2.1	118	78.5	4300	5300
6814N	70	90	10	0.6	12.1	11.9	7000	8100
6914N	70	100	16	1	23.7	21.1	6500	7700
16014N	70	110	13	0.6	26.8	23.6	6100	7100
6014N	70	110	20	1.1	38	31	6100	7100
6214N	70	125	24	1.5	62	44	5100	6300
6314N	70	150	35	2.1	104	68	4600	5400
6414N	70	180	42		140	99.5	3800	4500
6815N	75	95	10	0.6	12.5	12.8	6500	7600
6915N	75	105	16	1	20.8	19.7	6200	7200
16015N	75	115	13	0.6	27.6	25.3	5700	6700
6015N	75	115	20	1.1	39.5	33.5	5700	6700
6215N	75	130	25	1.5	49.5	49.5	4800	5600
6315N	75	160	37	2.1	113	77	4300	5000
6415N	75	190	45		154	115	3600	4300
6815N	80	100	10	0.6	12.7	13.3	6000	7100
6916N	80	110	16	1	27.6	25.3	5700	6700
16016N	80	125	14	0.6	32	29.6	5300	6300
6016N	80	125	22	1.1	47.5	39.5	5300	6300
6216N	80	140	26	2	72.5	53	4500	5300
6316N	80	170	39	2.1	123	86.5	4000	4800
6416N	80	200	48		163	125	3400	4000